



SeekerCAM: Space Cameras

> SeekerCAM-2 Camera

PRODUCT INFORMATION

- + Notable Features
 - + Cost optimized, rugged design
 - + GigE Vision 2.0.3 compliant
 - + 1 PPS time reference input
 - + Settable Time Epoch
 - + Hardware & software image triggers
 - + Health and status reporting
 - + Built in test for camera hardware verification




SeekerCAM-2



PRODUCT SPECIFICATIONS

RESOLUTION	5MP (2592 x 1944)
SHUTTER	CMOS rolling shutter, Global reset shutter
IMAGE DEPTH	12-bit, 1.4 V/lux-sec (500 n-m)
DYNAMIC RANGE	70.1 dB, Image SNR 38.1 dB
EXPOSURE TIMING PRECISION	1 μ -sec
EXPOSURE DURATION	0.1 – 5000 msec
LENS (C-MOUNT)	4.8, 8, 11, 70, 200 (mm) Custom sizes available upon request.
INPUT VOLTAGE	5.0 $\pm$ 0.3 VDC
AVERAGE POWER CONSUMPTION	2.5 W
OUTPUT FORMATS (GigE)	Mono8 (8 bit), Mono12 (12 bit)
WEIGHT (EXCL LENS)	150 g
ENVELOPE (EXCL LENS)	50 x 50 x 49 mm
SHOCK & VIBE	1550 g pyro-shock to 10,000 Hz, Vibration to 4.1 gRMS, 3-axes
OPERATING TEMPERATURE	-30 to 50°C
RADIATION (TID)	45 krad (Si)
DESCTRUCTIVE SEE	> 37 MeV-cm ² /mg



SeekerCAM-2



©Redwire Space. All rights reserved. v1_July 20, 2026 4:51 PM. The product information contained on this page is (i) an approximation based on current design plans, (ii) provided for informational purposes only, and (iii) subject to change without notice. This information does not constitute a guarantee, warranty, or representation of final product features, specifications, or performance. Actual features, specifications, and performance may vary due to product updates, design modifications, regulatory requirements, or other factors. Please contact us directly for the most up-to-date product details.