



SeekerTORCH: Lighting Solutions

> SeekerTORCH

PRODUCT INFORMATION

- + TRL 9 Flight Heritage
- + Natural White LED Floodlight
- + Built-in heater and temp sensor
- + 35 lux at 4 meters
- + Qualified in random vibration, shock, and TVAC environments
- + Radiation and EMI/EMC qualifications planned for the future

SeekerTORCH

NOTE: Floodlight in picture does not have cover or encapsulant applied to it yet.



PRODUCT SPECIFICATIONS

CORRELATED COLOR TEMPERATURE	6000K
BRIGHTNESS (ON-AXIS)	35 lx @ 4m
BRIGHTNESS (15° OFF-AXIS)	31 lx @ 4m
INPUT VOLTAGE (LIGHT)	28.0 ± 2.5 VDC
INPUT VOLTAGE (HEATER)	28.0 ± 2.5 VDC
INPUT VOLTAGE (THERMAL SENSOR)	5.0 - 30.0 VDC (12VDC nominal)
AVERAGE POWER CONSUMPTION	15 W
ELECTRICAL INTERFACE	9-Pin DSub
MECHANICAL INTERFACE	3x Through-Hole #6 Fasteners
WEIGHT	140 g
ENVELOPE	84.0 × 74.3 × 14.9 mm
SHOCK & VIBE	2,000g pyro-shock to 10,000Hz Vibration to 19.6 gRMs. 3 axes
OPERATING TEMPERATURE	-45°C to +55°C



©Redwire Space. All rights reserved. v1_July 20, 2026 4:51 PM. The product information contained on this page is (i) an approximation based on current design plans, (ii) provided for informational purposes only, and (iii) subject to change without notice. This information does not constitute a guarantee, warranty, or representation of final product features, specifications, or performance. Actual features, specifications, and performance may vary due to product updates, design modifications, regulatory requirements, or other factors. Please contact us directly for the most up-to-date product details.