




SentinelSUN: Quad Sun Sensor

> Quad Sun Sensor

The Quad Sun Sensor (QSS) uses a quad-element photodiode to measure the solar attitude angle in two axes.

PRODUCT INFORMATION


- + Buffered photo-diode outputs (four voltages) are processed by customer to determine solar attitude angle using Redwire-supplied transfer function and calibrated coefficients.



Quad Sun Sensor (QSS)

PRODUCT SPECIFICATIONS

ACCURACY	<1.5° (Center) <2.5° (±35° min.)
FIELD OF VIEW	±65°
ELECTRICAL INPUT	4 – 14 VDC
ELECTRICAL OUTPUT	4 Voltages
ELECTRICAL INTERFACE	9 Pin Micro-D Connector
MECHANICAL INTERFACE	3x Through-Hole #4 Fasteners
WEIGHT	50 g
ENVELOPE	38.1 x 44.5 x 19.8 mm
SHOCK & VIBE	1500 g pyro-shock to 10,000 Hz Vibration to 14.1 g _{RMS} , 3-axes
OPERATING TEMPERATURE	-40°C to +75°C
RADIATION	50 krad TID (Si)



Quad Sun Sensor (QSS)



©Redwire Space. All rights reserved. v1_06-24-2026. The product information contained on this page is (i) an approximation based on current design plans, (ii) provided for informational purposes only, and (iii) subject to change without notice. This information does not constitute a guarantee, warranty, or representation of final product features, specifications, or performance. Actual features, specifications, and performance may vary due to product updates, design modifications, regulatory requirements, or other factors. Please contact us directly for the most up-to-date product details.